
Technical Reference Manual

Introduction & HP Vectra Product Line Overview

<p>The Technical Reference Manual contains the following documents available on the <i>HP Information CD-ROM</i> or downloadable from the Web in PDF format:</p>
<p>Introduction & HP Vectra Product Line Overview The document you are reading. Describes how to use the Technical Reference Manual and provides an overview of VEi, VLi and VL600 PCs.</p>
<p>Product Description A separate document for VEi 7 models, VEi 8 models, VL600 models and VLi 8/VLi 8SF models, providing detailed BIOS information and summary information on the hardware components in the PC.</p>
<p>HP Vectra Technology A detailed look at the hardware components in all the PCs in the product line. Includes information on processors, chip sets, graphics controllers, network cards, connectors and sockets.</p>

HP Vectra

- VEi 7
 - VEi 8
 - VLi 8
 - VLi 8SF
 - VL600
-

HP Vectra Product Line Overview

This document provides a brief overview of the technical features and components of the following HP PCs:

- VEi 7 Desktops
- VEi 8 Desktops
- VLi 8 Desktops and Minitowers
- VLi 8 SF Desktops
- VL600 Desktops and Minitowers

HP Vectra Product Line Overview

Overview of the PCs in this Manual

Overview of the PCs in this Manual

HP Vectra VEi PCs

Component	VEi 7 (Desktop only)	VEi 8 (Desktop only)
Package Description	1 Or 2 Free Front-access shelves (one if a CD-ROM is fitted). Up to 4 Accessory board slots (3 PCI, 1 ISA).	1 Or 2 Free Front-access shelves (one if a CD-ROM is fitted) Up to 4 Accessory board slots (3 PCI, 1 ISA)
	Width: 41.8cm (16.5 in); Height: 14.0 cm (5.5 in); Depth: 37.5 cm (14.8 in).	
Processor	Intel® Celeron™ Socket 370 366/66, 400/66, 433/66, 466/66 when available (128 KB L2 cache).	Intel Pentium® II 350/100, 400/100 (512KB L2 cache). Intel Pentium III 450/100, 500/100 (512KB L2 cache).
System Board:		
Chip set	SiS 620/5595	Intel 440ZX/PIIX4E
Integrated I/O	On SiS 5595 chip. 2 USB connectors, 1 serial port and 1 parallel port	On PIIX4E chip. 2 USB connectors, 1 serial port and 1 parallel port.
Integrated IDE	On SiS 5595 chip. 2 IDE Ports (Ultra DMA/33)	On PIIX4E chip. 2 IDE Ports (Ultra DMA/33)
Integrated Graphics	SiS super AGP graphics controller (on SiS 620 Host chip) with 4 MB of video memory (upgradeable to 8MB)	Integrated Matrox® Millennium G200 2X AGP graphics controller with 8MB of video memory (not upgradeable)
Integrated Audio	CrystalClear™ CS4280 PCI audio controller/CrystalClear CS4297 Audio Codec '97	
Mass storage	Hard disks: 4.3 GB IDE, or 8.4 GB IDE. 6.4 GB IDE (accessory D8372A) Floppy drive: standard 1.44 MB 3.5" CD-ROM drive: 32X MAX IDE (selected models). Available as accessory (D4348A) DVD drive: accessory D6935A. ZIP drive: accessory D6650A.	
Main memory	Two DIMM sockets using: 32MB, 64MB, 128MB non-ECC 100MHz SDRAM or 256MB ECC 100MHz SDRAM to a maximum of 512MB. PC comes with a single 32MB or 64MB DIMM. Other DIMMs available as accessories.	
Expansion cards (available as accessories)	HP Adaptec 2940 UW SCSI board: accessory D6951A. HP Serial interface card: accessory D8388A. HP 10/100 3Com 3C905B-TX network interface card (on selected models). Also available as an accessory (single card: D7504A). HP 10/100 Intel Pro/100+ management adapter. Network card accessory D7506A (single card). HP 56K V90 PCI fax modem: accessory D7808A.	
Input devices	HP Standard Keyboard. HP Standard Mouse. HP Multimedia Keyboard: accessory C4742A. HP Scrolling Mouse: accessory C4736A.	
Power supply	Manually switched 115/230 VAC, 170 W input, 90 W output	
BIOS	Type: Phoenix BIOS Version: HX.07.xx Setup program: English only BIOS error messages: English only	Type: Award BIOS: Version: HW.27.xx Setup program: English only BIOS error messages: English only.

HP Vectra VLi PCs

Component	VLi 8 Desktop	VLi 8 Minitower	VLi 8 SF (Small Form Factor Desktop)
Package Description	1 Or 2 free front-access shelves (1 if a CD-ROM is fitted). The second shelf can also be used for a second hard drive. Up to 4 expansion slots (2 PCI, 1 ISA, 1 PCI-ISA combination slot).	2 Or 3 free front-access shelves (2 if a CD-ROM is fitted). One free internal shelf for a second hard drive. Up to 6 expansion slots (3 PCI, 3 ISA).	One or no free front-access shelves (none if a Slim CD-ROM is fitted). Up to 2 expansion slots (1 PCI, 1 PCI-ISA combination slot).
	Width: 44.3 cm (17.4 in); Height: 13.8 cm (5.4 in); Depth: 43.5 cm (17.1 in); Weight: 10.4 kg (22.9 pounds)	Width: 20.7 cm (8.1 in); Height: 46.9 cm (18.5 in); Depth: 45.5 cm (17.9 in); Weight: 14.8 kg (32.6 pounds)	Width: 37 cm (14.6 in); Height: 9.5 cm (3.7 in); Depth: 39 cm (15.4 in); Weight: 7.54 kg (16.5 pounds).
Processor	Intel Pentium II 400/100 (512KB L2 cache). Intel Pentium III 450/100, 500/100 and when available 550/100 (512KB L2 cache).		Intel Celeron Socket 370 366/66, 400/66 (128 KB L2 cache). Intel Pentium II 400/100 (512KB L2 cache). Intel Pentium III 450/100, 500/100 (512KB L2 cache).
System Board:			
Chip set	Intel 440ZX/PIIX4E		
Integrated I/O	On PIIX4E chip. 2 USB connectors, 2 serial ports and 1 parallel port.		
Integrated IDE	On PIIX4E chip. 2 IDE Ports (Ultra DMA/33)		
Integrated Graphics	Integrated Matrox Millennium G200 2X AGP graphics controller with 8MB of video memory (not upgradeable)		
Integrated Audio	CrystalClear CS4280 PCI audio controller/CrystalClear CS4297 Audio Codec '97		
Integrated Network	not available	not available	HP 10/100 3Com 3C905B-TX integrated on riser card
Mass storage	IDE Hard disks: 6.4GB or 8.4 GB. CD-ROM drive: 32X MAX IDE (selected models). Also available as accessory (D4348A). Floppy drive: standard 1.44 MB 3.5". DVD drive: accessory D6935A. ZIP drive: accessory D6650A.	IDE Hard disks: 6.4GB, 8.4GB or 13.5GB. CD-ROM drive: 32X MAX IDE (selected models). Also available as accessory (D4348A). Floppy drive: standard 1.44 MB 3.5". DVD drive: accessory D6935A. ZIP drive: accessory D6650A.	IDE Hard disks: 4.3GB or 8.4GB. 6.4GB available as accessory (D8372A). Slim CD-ROM drive: 24X MAX IDE (selected models). Also available as accessory (D8381A). Floppy drive: standard 1.44 MB 3.5".
Main memory	Two DIMM sockets using: 32MB, 64MB, 128MB non-ECC 100MHz SDRAM or 256MB ECC 100MHz SDRAM to a maximum of 512MB.		
	Comes with a single 64MB DIMM. Other DIMMs available as accessories.		Comes with a single 32MB or 64MB DIMM. Other DIMMs available as accessories.
Expansion cards (available as accessories)	HP 10/100 3Com 3C905B-TX network interface card (on selected models). Also available as accessory (single card: D7504A). HP 10/100 Intel Pro/100+ management adapter. Network card, available as an accessory (single D7506A). HP 56K V90 PCI fax modem. Accessory D7808A.		HP 10/100 Intel Pro/100+ management adapter. Network card, available as an accessory (single card D7506A). HP 56K V90 PCI fax modem. Accessory D7808A.
Input devices	HP Standard Keyboard; HP Standard Mouse; HP Multimedia Keyboard: (accessory C4742A); HP Scrolling Mouse (accessory C4736A).		
Power supply	Manually switched 115/230 VAC, 170 W input, 120 W output (max)	Manually switched 115/230 VAC, 170 W input, 120 W output (max)	Manually switched 115/230 VAC, 170 W input, 90 W output (max)
BIOS	Type: HP/Phoenix; Version: HZ.01.xx; Setup Program: English only; BIOS error messages: Available in French, German, Spanish, Italian, Danish, Dutch, Finnish, Norwegian, Portuguese, Swedish, English.		

HP Vectra Product Line Overview

Overview of the PCs in this Manual

HP Vectra VL600 PCs

Component	VL600 Desktop	VL600 Minitower
Package Description	1 Or 2 Free Front-access shelves (one if a CD-ROM, DVD-ROM or CD-RW is fitted). Up to 7 Accessory board slots (4 PCI, 2 ISA, 1 AGP).	2 Or 3 Free Front-access shelves (two if a CD-ROM, DVD-ROM or CD-RW is fitted) Up to 7 Accessory board slots (4 PCI, 2 ISA, 1 AGP).
	Width: 43.5 cm (17.13 in); Height: 13.5 cm (5.32 in); Depth: 43 cm (16.93 in).	Width: 20.6 cm (8.1 in); Height: 46.9 cm (18.5 in); Depth: 45.5 cm (17.9 in).
Processor	Intel Pentium III 533EB/133, 550/100, 600/100, 600EB/133, 667/133, 700/100, 733/133.	
System Board:		
Chip set	Intel® i820	
Integrated I/O	On ICH chip. 2 USB connectors, 2 serial ports and 1 parallel port.	
Integrated IDE	On ICH chip. 2 IDE Ports (Ultra DMA/66)	
Integrated Graphics	Matrox® G250 2X AGP graphics controller with 8MB of video memory (upgradeable to 16 MB). Matrox® Millennium G400 4X AGP graphics controller with 32MB of video memory (non-upgradeable).	
Integrated Audio	CrystalClear™ CS4280 PCI audio controller/CrystalClear CS4297 Audio Codec '97	
Mass storage	Hard disks: 10GB IDE, 15GB IDE, 30GB IDE, 9.1GB SCSI Floppy drive: standard 1.44 MB 3.5" CD-ROM drive: 48X max IDE (in selected models). Also available as accessory (D9444A) DVD drive: 8x, 40x (in selected models) Also available as accessory (D7521A) CD-RW drive: 4x, 2x, 20x (in selected models). Also available as accessory (D9524A) ZIP drive: accessory D9446A.	
Main memory	Two RDRAM sockets using: 128MB, 256MB or 512MB RDRAM (when available) to a maximum of 1024MB. PC comes with a single 128 MB module. Other modules available as accessories.	
Expansion cards (available as accessories)	HP Ultra II SCSI adapter card: accessory D9529A. HP 10/100 3Com 3C905C-TX network interface card (on selected models). Also available as an accessory (single card: D7522A). HP 10/100 Intel Pro/100+ management adapter (on selected models) . Also available as an accessory (single card: D7506A). HP 10/100BT PCI Ethernet Card: accessory D7508A HP 56K V90 USB fax modem: accessory D8384A.	
Input devices	HP Standard Keyboard HP Multimedia Keyboard: accessory C4742A. HP Standard Mouse HP Scrolling Mouse: accessory C4736A.	
Power supply	Manually switched 115/230 VAC, 170 W input, 120 W output (max)	Manually switched 115/230 VAC, 310 W input, 200 W output (max)
BIOS	Type: Phoenix BIOS Version: hy.01.xx Setup program: English only BIOS error messages: Available in French, German, Italian, Spanish, Danish, Dutch, Finnish, Portuguese, Norwegian, Swedish, English.	

The Technical Reference Manual

This *Technical Reference Manual* is a technical reference and BIOS document for personnel providing system level support. It is presented in modular form to provide quick and easy access to technical information on HP Vectra VEi 7, VEi 8, VL600 and VLi 8/VLi8 SF PCs. It is made up of the following components:

- *HP Vectra Product Line Overview*. This document provides a quick reference guide to the BIOS and hardware components in each PC. It also lists some of the available accessories.
- *Product Description*. Provides technical information specific to a particular PC. This includes summary information on product hardware and detailed information on the PC's BIOS. Read this manual to see which hardware components are in the PC.

Separate *Product Description* manuals exist for:

- VEi 7 models
- VEi 8 models
- VLi 8 and VLi 8SF models
- VL600 models
- *HP Vectra Technology*. An in-depth guide to the hardware in all of the featured Vectra PCs. Subjects covered include chip sets, processors, graphics controllers, hard disk drives and DVD drives.

Technical information that is readily available from other sources, such as manufacturer's proprietary publications has not been reproduced.

The *Technical Reference Manual* contains summary information only. For additional reference material, refer to the bibliography at the beginning of the *Product Description* and *HP Vectra Technology* manuals.

Conventions

The following conventions are used throughout this manual to identify specific numeric elements:

- Hexadecimal numbers are identified by a lower case h.
For example, 0FFFFFFFh or 32F5h
- Binary numbers and bit patterns are identified by a lower case b.
For example, 1101b or 10011011b

Notice

The information contained in this document is subject to change without notice.

Hewlett-Packard makes no warranty of any kind with regard to this material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose.

Hewlett-Packard shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

Hewlett-Packard assumes no responsibility for the use or reliability of its software on equipment that is not furnished by Hewlett-Packard.

This document contains proprietary information that is protected by copyright. All rights are reserved. No part of this document may be photocopied, reproduced, or translated to another language without the prior written consent of Hewlett-Packard Company.

Adobe® and Acrobat® are registered trademarks of Adobe Systems Incorporated which may be registered in certain jurisdictions.

Microsoft®, Windows® and MS-DOS® and Windows NT® are U.S. registered trademarks of Microsoft Corporation.

Netscape™ is a U.S. trademark of Netscape Communications Corporation.
MMX™ and Celeron™ are trademarks and Intel® and Pentium® are registered trademarks of Intel Corporation.

Matrox® is a registered trademark of Matrox Electronics Systems Limited.

CrystalClear™ is a trademark and Crystal® is a registered trademark of Cirrus Logic Incorporated.

DVDExpress™ is a trademark of Mediomatics Incorporated.

Kensington™ is a trademark of Kensington Microware Ltd.

Hewlett-Packard France
Business Desktop Division
38053 Grenoble Cedex 9
France

